Laserliner®

BBQ-GasCheck



Measuring device for determining the level in LPG cylinders

Rev.1116







- For determining the level in LPG cylinders made from **steel and aluminium**
- **Visual and acoustic signal** for indicating level
- **Auto shut-off function**
- Applications: e.g. camping, for radiant heaters or joining bitumen sheets

TECHNICAL DATA

ALUMINIUM/STEEL CYLINDER DIAMETER 200 mm … 350 mm
OPERATING TEMPERATURE 0°C … 40°C
STORAGE TEMPERATURE -10°C … 70°C
POWER SUPPLY 9V E block ANSI/NEDA 1604, 1604A; IEC 6LR61, 6F22
OPERATING TIME approx. 30 h
DIMENSIONS (W x H x D) 146 x 46 x 30 mm
WEIGHT (incl. battery) 99 g



Scan



Full



Empty



BBQ-GasCheck
+ battery

Packing dimension (W x H x D)
–

ARTICLE	ARTICLE NO	EAN-CODE	PU
BBQ-GasCheck	082.161A	4 021563 696482	5

9V AutoSound

UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · laserliner@umarex.de · www.laserliner.com