Leica LINO Product Comparison Table



Applications		P5	L2	L2G	L2P5	L2P5G	L6R	L6G
General important aspects	Green laser for better point and line visibility			●		●		●
	Recommended maximum working range	30 m	25 m	35 m	25 m	35 m	25 m	35 m
	Levelling accuracy	± 0.2 mm/m	± 0.2 mm/m	± 0.2 mm/m	± 0.2 mm/m	± 0.2 mm/m	± 0.2 mm/m	± 0.2 mm/m
Horizontal	Alignment	(●)	●	●	●	●	●	●
	Transferring heights	(●)	●	●	●	●	●	●
	Fine adjustment for e.g. suspended ceilings		●*	●*	●*	●*	●*	●*
Vertical	Alignment	(●)	●	●	●	●	●	●
	Fine adjustment manual						●	●
Plumbing	Transferring points from floor to ceiling	●			●	●	(●)	(●)
Slopes	Lock laser for slope alignment		●	●	●	●	●	●
Stake-out	Rectangular angles	●			●	●	●	●
Usability	Extra long operation with Li-Ion power	●**	●**	●**	●	●	●**	●
	Operation during charging	●**	●**	●**	●	●	●**	●
	Alternative usage with Alkaline batteries	●	●	●	●	●	●	●
	Easiest setup to adapter with magnets	●	●	●	●	●	●	●
	Range extension with receiver		●	●	●	●	●	●

*) UAL 130 accessory required

**) Li-Ion accessory required

Leica Geosystems